CLEAN AIR SYSTEMS



HORIZONTAL LAMINAR AIR FLOW CABINET

TFT Touch Screen Display Controller with Air Velocity Sensor MSW-161(TFT)



- Designed so as to meet the requirements of US Federal Standard 209 B(BS 5295) providing particle free air to meet class 100 conditions.
- Cabinet is fabricated of CRC Sheet duly powder coated OR stainless steel (SS-304grade) (as ordered).
- Working table is made of Stainless Steel Sheet (SS-304 grade).
- Front doors are made out of thick transparent toughened glass.
- Heavy Duty Motor operates with minimum noise level.
- Working area is illuminated by fluorescent lighting fitted to the unit.
- Supplied complete with S.S. Satin finish Table Top, Transparent front door, Built in U.V. Germicidal light and Cock for gas, air or vacuum line, HEPA filters and pre-filter.
- Air drawn through pre-filter is made to pass through highly effective HEPA (High Efficiency Particular Air) filters. The prefilter fitted extends
 the life of HEPA filter drastically. Fitted with HEPA Filter made from water resistant, fire retardant, imported micro fine glass fibre media;
 conforms to EU 14 Grade, with an efficiency rating better than 99.999% for 0.3 μ. These filters are designed to accommodate higher airflow
 volume.
- Prefilter are made from Non-Woven Synthetic with HDPE mesh and AI expanded mesh on air leaving side; conforms to EU 6 Grade, with efficiency of 95% down to 5 micron. These filters can be cleaned by compressed air & also washable.
- Mounted on heavy tubular stand with levelers
- With Solid Side Walls and transparent front door.
- Towork on 220/230 volts A.C. supply.

TECHNICAL SPECIFICATIONS & ORDERING INFORMATIONS

MODEL	#LH-22(CRC-TFT)	#LH-32(CRC-TFT)	#LH-42(CRC-TFT)	#LH-62(CRC-TFT)
MODEL	#LH-22(SS-TFT	#LH-32(SS-TFT)	#LH-42(SS-TFT)	#LH-62(SS-TFT
Internal Dimensions (WxDxH)mm	600x610x675mm	900x610x675mm	1200x610x675mm	1780x610x675mm
No. of HEPA Filter	1	1	1	2
Main Filter	HEPA Filter made from water resistant, fire retardant, imported micro fine glass fibre media; conforms to EU - 14 Grade, with an efficiency rating better than 99.999% for 0.3 μ. These filters are designed to accommodate higher airflow volume.			
Pre - Filter	Prefilter are made from Non-Woven Synthetic with HDPE mesh and Al expanded mesh on air leaving side; conforms to EU 6 Grade, with efficiency of 95% down to 5 micron. These filters can be cleaned by compressed air & also washable.			
Controller	TFT Touch Screen Display Controller with air velocity sensor			
Illumination	Fluorescent Lamp 40W			
Sterilizing	UV Germicidal Tube			
Front Door	Made of plexi glass (polycarbonate door optional)			
Utility	Gas/Air Cock			
Power Supply & Frequency	AC 230V, 50/60 Hz			
MOC (Cabinet)	CRC Sheet Duly Powder Coated or Stainless Steel (SS-304)			
Work Table	Stainless Steel (SS-304)			

OPTIONS

- a) Magnehelic Gauge (To track filter pressure) to cost extra.
- b) Electronic Filter choke alarm. (Differential pressure monitor)
- c) Medical lockable castor in lieu of adjustable levellers to cost extra.
- d) Gas Burner.
- e) Exhaust ducting per running feet.

- f) Motorized sash lift in lieu of manual sash lift to cost extra.
- g) UV Hour meter
- h) Extra power outlet switch
- i) DOP HEPA filter testing in house.
- j) DOP HEPA filter testing on site.



B-35/3, G.T. KARNAL ROAD, INDUSTRIAL AREA, DELHI - 110033

Tel: +911148494849 (100 Lines)

E-mail: info@macroscientificworks.com Web: www.macroscientificworks.com